

### Highlights:



---

- 24 AWG thin and dense stranded conductors
- Highflex™ solid & flexible jacket
- 6.2 mm (Ø) outer diameter
- Made in EU

### Product information:

---

The PMI224 is a high-quality microphone cable with a highly flexible outer jacket. This cable is made rigid, which allows you to roll it up, even at longer lengths effortlessly. Two 24 AWG (0.22 mm<sup>2</sup>) conductors consisting of 12 copper strands with 0.15 mm thickness are surrounded by an 80-strand braided copper shielding with superior coverage. Combined with the thick and soft PVC outer jacket, this provides a flexible but solid feel while allowing it to withstand an extreme amount of bending cycles. Optimal signal transmission is guaranteed due to the low capacitance and use of high-purity copper, while the high-coverage shielding provides excellent immunity against interference. These features make the PMI224 perfect for use in professional stage & studio applications.



### Certification:

---



### Properties:

---



## Inner Conductors:

---



## Shielding:

---



## Product Features:

---

Application	Rental & MI
Series	Bulk & Accessories

## Physical Characteristics:

---

Inner conductor	Insulation	Material	PE 1.5 mm (Ø)
		Colours	White / Red
	Shielding	Braiding	BC 16 x 5 x 0.10 mm (Ø) (OFC)
Outer jacket	Material		Highflex PVC 6.2 mm (Ø)
	Colours		Black
Type of cable			24 AWG Microphone cable
Inner conductor	Material		BC 12 x 0.15 mm (Ø) (OFC)
	Section		0.22 mm <sup>2</sup>
Filling			Cotton Yarn
Inner conductor	Number of conductors		2
	Conductor twisting		Yes

## Mechanical Characteristics:

---

Temperature range Fixed installation - 20 °C till + 70 °C

Mobile installation - 5 °C till + 70 °C

Bending radius Fixed installation 5 x outer diameter

Mobile installation 10 x outer diameter

## Variants:

---

- PMI224/1 - 100 meters
- PMI224/3 - 300 meters