

CANNON C4i

HIGH FIDELITY COAXIAL INSTALLATION SPEAKER ENCLOSURE



FEATURES

- 4" + 1" Coaxial Transducer
- 4" Passive Radiator
- Bass Response Down to 100 Hz
- 85° Conical Coverage Pattern
- High Fidelity
- IP55 + Salt Water Resistant

APPLICATIONS

- Restaurants
- Retail
- Monitors
- Front Fills

DESCRIPTION

The C4i is a unique point source, coaxial loudspeaker. This model is extremely light, compact and discreet. Each Cannon model utilizes a low frequency driver with a coaxially mounted 1" silk dome high frequency driver. The Cannons' silk dome driver is a purpose-built, ferrofluid-cooled design that enables high sound pressure levels, with improved sound quality, as well as consistency and durability over time. The enclosure also incorporates a rear-facing passive radiator specifically tuned to extend the bass frequency response. These key features allow the C4i to provide the sound quality of a studio monitor.

The C4i features a screw terminal block connector, with parallel link output. The C4i is also available in the C4 version, which has a marine grade cable gland with 16/2 gauge wire, as well as the C4m version that has a marine grade cable gland with 16/2 gauge wire and all stainless steel 316 metal parts.

SPECIFICATIONS


Audio Specifications

- Description:** Passive 4" coaxial with a 4" passive radiator
- Bandwidth:** 100 Hz - 18 kHz (-6 dB)
- Max SPL:** 111 dB SPL @ 1 m w/ preset
- Power:** 200 watts (continuous), 100 watts (AES)
- Directivity:** 85° conical
- Elements:** (1) 4" coaxial with a 1" dome high frequency element, (1) 4" passive radiator
- Impedance:** 8 Ω
- Connectors:** (1) screw terminal block with input +/- and link +/-


Mechanical Specifications

- IP Rating:** IP55 indoor
- Rigging:** (4) M6 points
- Weight:** 5.1 lb / 2.3 kg
- Construction:** Finland birch plywood (phenolic resin), three coats of polyurea, matte salt and UV resistant coating, A4 (316) stainless steel hardware, galvanized and powder-coated black or white steel input plate, 3D spacer mesh fabric
- Dimensions:** 5.9" (150 mm) x 5.9" (150 mm) x 7" (180 mm)
- Colors:** Stocking black and white, custom colors and fabrics available
- Accessories:** C-Clamp (wall-, truss-, mic stand- or ceiling-mount), Universal Mounting Plate, Pole Mount Adaptor, L-Bracket, Tube Mount, Swivel Mount



DIRECTIVITY



FREQUENCY RESPONSE




WIRING



Terminals:
 1+ Positive full range
 1- Negative full range
 1+ Positive (parallel link)
 1- Negative (parallel link)





Screw terminal input/link wiring



Euroblock 4/8-p amplifier output wiring

DIMENSIONS

RIGGING



(4) points M6
 • Bottom: (2) points M6 – for mounting plate and pole mount
 • Sides: (2) points M6 – 1 each side for C-Clamp

ACCESSORIES



Contact

For more product or service information please contact the 1 SOUND headquarters.

1 SOUND, Manufacturer
 USA Distributor
 34 Apple Street
 Tinton Falls, NJ 07724

tel. +1-732-798-9900
 sales@1-sound.com

Warranty

All manufactured 1 SOUND products are warranted to be free from defects in materials or workmanship for a period of 3 years from original purchase. If there is specific hardware or grilles you might want replaced or any repairs needed please contact your region's authorized 1 SOUND distributor.

