



Sound Devices  
MixPre II Series  
MixPre-10 II  
Technical Datasheet

## Audio Inputs

- Frequency Response: 10 Hz to 80 kHz +/- 0.5 dB re 1 kHz @ 192 kHz sample rate
- THD + Noise: 0.005% max (@1kHz, 22-22 kHz BW, gain=20 dB, -10 dBu in)
- ADC: 32 bit precision; 142 dB dynamic range min (A-weighted, gain=10 dB, fader=0 dB)
- Equivalent Input Noise: -130 dBV (-128 dBu) max (A-weighting, gain=76 dB, 150 ohm source impedance)

## Inputs

- Mic: XLR active-balanced; 4k input
- Line: XLR active-balanced; 4k input
- Aux/Mic in: 3.5 mm TRS, 2-channel unbalanced; 2.2k
- Line: ¼-inch TRS active-balanced; 4k input
- USB Audio: 4 channels
- 10 Total analog inputs: 8 mic-line inputs, 2 on Aux In
- All inputs fully RF-filtered and overload protected.

## Gain

- Mic input: +6 dB to +76 dB
- Line input: -20 dB to +30 dB
- Fader: -inf to +20 dB
- Headphone: -inf to +20 dB
- Total, Mic-to-recording (max): +96 dB
- Aux In (Mic): Gain = +10 dB to +40 dB
- Aux In (Line): Gain = -10 dB to +20 dB
- Total Aux Gain including Fader (Mic-to-recording): +60 dB

## Maximum Input Level

- Mic XLR: +14 dBu (limiters on or off)
- Line XLR/¼-inch: +28 dBu (limiters on or off)
- Aux In (Mic): -10 dBu
- Aux In (Line): +10 dBu

## Low Cut Filters

- 40 Hz to 160 Hz (adjustable), 18 dB/oct. First stage analog, subsequent stages digital.

## Microphone Powering

- Mic XLRs: 48 V via 6.8k resistors, 10 mA each
- Mic 3.5 mm: 3 V @ 3k source

## Limiters

- Limiter at all gain stages, range > 40 dB. First stage analog, subsequent stages digital. Adjustable Threshold, Ratio, and Release.

## Audio Outputs

- DAC feeding Stereo Out, Headphone Out: 32 bit precision; 115 dB dynamic range (A-weighted)
- L/R Out: TA3 2-channel balanced, 1.1K max output impedance, +18 dBu max output level
- X1/X2 Out: 3.5 mm TRS stereo unbalanced, 500 ohm output impedance, +7.8 dBu max output level
- Headphones Out: 3.5 mm TRS stereo unbalanced, 300 mW + 300 mW, for use with any impedance headphones

## USB

- Audio Interface (USB-C): 12-in/4-out; 44.1 to 96 kHz; 16/24/32-bit integer, 32-bit float; Class-compliant USB 2.0 high speed or ASIO® driver (supplied via download)
- Mass Storage (USB-C): USB 2.0 high speed
- Keyboard (USB-A): Text entry and control
- Thumbdrive (USB-A): Manual or auto-copy to drive
- Midi Control Surface (USB-A)

## Recording

### Maximum Record Tracks

- 12 Tracks: Stereo mix + 10 ISOs

### Sampling Frequency

- 44.1 kHz
- 47.952 kHz
- 48 kHz
- 48.048 kHz
- 96 kHz
- 192 kHz

### Bit Depth

- 16
- 24
- 32 Float

## Recording Storage

- Type: SD, SDXC, SDHC Card (USB thumbdrive, copy only)
- Max Storage Size: 512 GB (SDXC)
- Card format: exFAT

## File Types

- Polyphonic WAV

## Timecode

### Timecode Modes

- Free Run
- Time of Day (file stamped w/current ToD)
- Rec Run
- Ext LTC (file stamped w/incoming LTC on BNC or Aux 3.5mm)
- Camera TC (file stamped w/incoming TC from cameras that output TC)

### Timecode Frame Rates

- Auto-detects (fps):
- 23.98 (same as 23.976)
- 24
- 25
- 29.97DF
- 29.97ND
- 30
- 30DF

### Sync Source

- Internal, Word Clock, Ext LTC

### BNC In (TC In)

- Switchable between Timecode (default) or Word Clock Input
- Timecode: 20k ohm impedance, 0.3 V – 3.0 V p-p (–17 dBu – +3 dBu)
- Word Clock: 10k ohm impedance, 1.5 V p-p

### BNC Out (TC Out)

- Switchable between Timecode (default) or Word Clock Output
- Timecode: 1k ohm impedance, 3.0 V p-p (+12 dBu)
- Word Clock: 75 ohm impedance, 5 V p-p

## HDMI

- TC Reader via HDMI

### Sample/Timecode Accuracy

- 0.2 ppm (0.5 frames per 24 hours)

## Remote Control

- Bluetooth LE: Wireless control using Wingman app
- HDMI (micro): Auto-record start/stop trigger from cameras that output record flag over HDMI
- Timecode: Auto-record start/stop trigger via Aux In timecode

## File Delivery to Cloud

- Compatible with Viviana Cloud

## Touch Screen

- 320×256; 1.6-inch, color, sunlight-viewable IPS LCD

## Power

- AA Batteries: 8x AA sled (included). NiMH recommended
- L-Mount: Optional sled for 2x (hot-swappable) Li-ion batteries
- AC Adapter: XL-WPH3 (included): Universal, 45 W in-line AC-to-DC power supply Hirose 4-pin DC plug, with detachable IEC power cord. 100-240, 50/60 Hz

## Environmental

- Operating: -20°C to 60°C, 0 to 90% relative humidity; (non-condensing)
- Storage: -40°C to 85°C

## Dimensions (H x W x D)

- 3.6 cm x 20.6 cm x 17.5 cm
- 1.375" x 8.125" x 6.875"

## Weight

- 0.91 kg (unpackaged, without batteries)
- 32.1 oz. (unpackaged, without batteries)