

Highlights:

- High quality back electret condenser capsule with cardioid pickup pattern
- Level & status indication LED's
- Tiltable pipe-neck microphone
- SurfaceTouch™ front panel
- Capacitive & illuminated selection buttons (4x)

Product information:

The MPX series are paging microphones specifically designed for use in combination with MTX series audio matrix systems. The MPX48 is the 4-zone system allowing it being used in combination with an MTX48 4-zone audio matrix system. The modern shaped enclosure is finished with a real glass front panel provided with an anti-glare coating. This offers a microphone with elegant outlook which will be appreciated in any office or even design interior environment. The controls are integrated in the glass panel through capacitive touch button principle without any mechanically moving parts, same as the indicator LED's which are completely blended. This guarantees a real high-end outlook and user experience. An integrated chime tone is audible before each announcement. Announcements are made through the integrated pipe-neck microphone with a cardioid pickup pattern, which can be tilted to the desired angle. Both zone selection and data bus indicators are implemented, giving an overview of the systems current operation mode and data bus occupation. Quick operation is made possible using the 'select' & 'clear all' buttons, while the 'push-to-talk' (PTT) button must be pressed during announcements. Connection to the matrix system is done through a fixed connection cable with a length of 2 meter. This distance can be extended to a maximum length of 300m using standard CAT5E (or better) twisted pair cabling. Cascading multiple paging stations is possible using the priority-based (user-configurable) databus, when using the additional junction box ARJ03P.

Applications:

- Corporate
- Sporting facilities



System specifications:

Microphone	Type	Back electret condenser
	Length	250 mm
Frequency	Response (± 3 dB)	50 Hz - 16 kHz
Sensitivity (1W/1m)		45 dB
Sound Pressure (Max. W/1m)		130 dB
Power	Consumption	1.5 W
	Supply	24 V DC (from MTX)
Connectors		RJ45 (Fixed 2 m cable)
Polar Pattern		Cardioid

Product Features:

Dimensions		221.5 x 43 x 111.6 mm (W x H x D)
Weight		0.330 kg
Construction		ABS
Databus	Control	RS-485
	Audio	Differential analogue
Colours		Black (RAL9004)
Paging Zones		4 Zones (use with MTX48)
Accessories	Included	Windscreen
		Connection cable 2 meter(fixed)

Shipping & Ordering:

Packaging	Cardboard box
Shipping weight & volume	2.000 kg - 0.0012 Cbm


Architects' and Engineers' Specifications:

The digital paging microphone shall be a four zone system for use in combination with 4-zone audio matrix systems. It shall contain a pipe-neck microphone fitted with a back electret condenser element with cardioid polar pattern which can be tilted to the correct angle.

The system shall be housed in a modern shaped enclosure finished with a real glass front panel with anti-glare coating. Controls for zone selection, 'PTT' (Push To Talk), 'Select all' and 'Clear all' shall be provided and blended in the glass front panel using a capacitive touch principle without any mechanically moving parts. Indicator LED's for zone selection and databus occupation shall also be completely blended. An integrated chime tone shall be heard before any announcement.

Connection with the matrix system shall be done using a fixed connection cable (2 meter) with an RJ45 type connector. The cabling shall include differential analogue audio, power distribution and RS-485 communication signals and shall be extendable up to a length of 300 meters over standard CAT5E (or better) cabling.

The system enclosure (base) shall be constructed of ABS (weighted) materials with 221.5 x 43 x 11 .6 mm dimensions and the net weight shall not exceed 0.375 Kg. The length of the pipe-neck microphone shall measure 250 mm.



<p>MPX48</p>	<p>Product description: 4-ZONE PAGING MICROPHONE FOR MTX48</p>
<p>Weight: 0,33 kg</p>	<p>Outer dimensions: (w x h x d) 208,6 x 43,8 x 111,6</p>
<p>Unit height: N/A</p>	