



Type(s)
Project
Date
Notes

GENERAL INFORMATION

DMX Widgets allow you to easily expand your console’s DMX output. Simply attach a USB DMX Widget and - just like that - you have more DMX outputs. Each standard DMX Widget adds one universe. The DMX Super Widget adds four ports and universes.

The MIDI/LTC Widget provides a single Linear Timecode input and MIDI in/out/thru for any Hog 4 OS consoles and any Hog 4 PC.

PRODUCT FEATURES (DMX WIDGETS)

- USB connection to any Hog 4 console, HPU and Hog 4 PC
- Single DMX-512 output per 5-pin XLR connector
- Multiple USB DMX Widgets can be connected via USB Hub
- Kensington security slot

PRODUCT FEATURES (MIDI/LTC WIDGET)

- One USB input connector providing power
- One Linear Timecode (LTC/SMPTE) input on 3 pin XLR connector
- MIDI in/out/thru supporting MIDI messages, MIDI Show Control, and MIDI Time Code
- Multiple USB MIDI/LTC Widgets can be connected via USB Hub
- Kensington security slot

ORDERING INFORMATION

Widgets

MODEL	DESCRIPTION
74040011	USB DMX Widget
74040008	USB DMX Super Widget
74040009	USB MIDI/LTC Widget



SPECIFICATIONS

DMX WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console, HPU and Hog 4 PC
- Rugged, stackable aluminum housing
- Single DMX-512 output on 5-pin XLR connector
- Supports up to 512 output channels
- One USB input connector providing power
- Multiple USB DMX Widgets can be connected via USB Hub
- Kensington security slot
- Storage Temperature 20° to 60°C (0° to 140°F)
- Compliance: ETL, CETL, CE

DMX SUPER WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console, HPU and Hog 4 PC
- Rugged, stackable aluminum housing
- Four DMX 512 outputs on 5-pin XLR connectors
- Supports up to 2,048 output channels
- One USB input connector
- Multiple USB DMX Widgets can be connected via USB Hub
- Kensington security slot
- External PSU included
- Storage Temperature 20° to 60°C (0° to 140°F)
- Compliance: ETL, CETL, CE

MIDI/LTC WIDGET SPECIFICATIONS

- USB connection to any Hog 4 console, HPU and Hog 4 PC
- Rugged, stackable aluminum housing
- One USB input connector providing power
- One Linear Timecode (LTC/SMPTE) input on 3 pin XLR connector
- MIDI in/out/thru supporting MIDI messages, MIDI Show Control, and MIDI Time Code
- Multiple USB MIDI/LTC Widgets can be connected via USB Hub
- Kensington security slot
- Storage Temperature 20° to 60°C (0° to 140°F)
- Compliance: ETL, CETL, CE

PHYSICAL

WIDGETS DIMENSIONS

MODEL	HEIGHT		WIDTH		DEPTH		WEIGHT	
	in	mm	in	mm	in	mm	lb	kg
DMX Widget	1.8	45	2.5	65	4.2	106	0.8	0.3
DMX Super Widget	1.8	45	7.8	198	4.2	106	1.1	0.5
MIDI/LTC Widget	1.8	45	7.8	198	4.2	106	1.1	0.5



Corporate Headquarters • Middleton, WI USA
Global Offices • London, UK • Rome, IT • Holzkirchen, DE • Paris, FR • Hong Kong
 Dubai, UAE • Singapore • New York, NY • Orlando, FL • Los Angeles, CA • Austin, TX
 Copyright©2023 ETC. All Rights Reserved. All product information and specifications subject to change. Rev B 2023-01
 *Trademark and patent info: etcconnect.com/IE

etcconnect.com