

B BLINDED1



SPECSHEET



1 x 110W LED Stage Blinder - Warm White with Amber drift

The Luxibel B BLINDED1 redefines stage lighting with its single blinder setup, powered by a 110W LED that delivers both warm white and amber drift. Ideal for creating an enchanting atmosphere on stage, it features advanced tungsten emulation technology, offering the charm of traditional lighting with modern efficiency.

Designed to withstand diverse weather conditions with an IP65 rating, the B BLINDED1 combines durability with performance, making it a versatile choice for both indoor and outdoor events. Its compact yet powerful output ensures a captivating presence, making it an essential addition to any lighting setup.



Physical

Dimensions (WxHxD):	247 x 234 x 150 mm 9.7 x 9.2 x 5.9 in
Packaging dimensions (WxHxD):	400 x 300 x 220 15.7 x 11.8 x 8.66 in
Net weight:	3.4kg 7.5 lb
Gross weight:	3.8kg 8.4 lb
Outer packaging gross weight:	17.3 kg 38.14 lbs (4 Pcs)
Outer packaging dimensions:	640 x 425 x 670 mm 22.20 x 16.73 x 26.38 in (4 Pcs)

Mounting options

Hanging:	1 x Omega bracket with 2 x 1/4 turn quick-locks and 1 x M12 hole
Second suspension:	Use the double bracket to sling the safety wire or carbinier
Standing:	Double bracket adjustable opening angle

Control

Menu control:	OLED display with 4 buttons
Control:	DMX512, manual, RDM
In/Link:	XLR 5-pin
DMX Mode:	1/2/4 channels
Dimming:	8 or 16-bit
Dimming curve	3 curves (fast , smooth or under)
Tilt locking system:	Two sided tilt locking

Optical

Beam angle:	50°
Colours:	Warm white & Red: 2,700K - 1,200K in Tungsten mode
Refresh rate:	1,200 Hz
Strobe:	Adjustable speed + random
CRI:	81.9 Ra
Light Output	Light output @ 50° 2m: 2,027 lux 4m: 540 lux 6m: 240 lux

Electrical

Fixture rated power:	110W
LED engine:	CREE LED 125W Flickerfree
Input power:	100 - 240V ~ 50/60Hz Auto switching power supply
In/Link:	powerCON TRUE 1 max. link current 10A
Power Factor:	0.97
LVI:	n/a

Environmental

Cooling:	Electronic heat control
IP rating:	IP65
Max. environment temperature:	40°

Accessories

Included	Omega bracket, powerCON True1
Optional	B FBDBLINED1