

B PANEL120WW



SPECSHEET

Warm White LED Soft Light



The B PANEL120WW offers great versatility and performance as a compact warm white soft light, perfect for TV productions, theater settings, and photography sessions. Its array of features includes barn doors, a removable frost and gel frame for light shaping, and manual or DMX control for brightness adjustment.

Equipped with an adjustable refresh rate to ensure flicker-free operation, the B PANEL120WW is an essential tool for professionals seeking a reliable and versatile lighting solution. Its design and functionality make it well-suited for a wide range of indoor applications.



Physical

Dimensions (WxHxD):	331 x 238 x 114 mm 13.03" x 9.37" x 4.49"
Packaging dimensions (WxHxD):	360 x 290 x 175 mm 14.17" x 11.42" x 6.89"
Net weight:	4.6 kg 10.14 lbs
Gross weight:	5.5 kg 12.13 lbs
Outer packaging gross weight:	11 kg 24.25 lbs (2 Pcs)
Outer packaging dimensions:	380 x 370 x 320 mm 14.96" x 14.57" x 12.60" (2 Pcs)

Mounting options

Hanging:	3 x M12 hole
Second suspension:	1 x Eye in back of unit to pass carabiner
Standing:	n/a

Control

Menu control: Control:	TFT 4 digit display with 4 buttons DMX512, manual dimming button
In/Link:	XLR 5-pin
DMX Mode:	1/2/3 channels
Dimming:	16-bit
Dimming curve	Linear
Tilt locking system:	Two sided tilt locking

Optical

Beam angle:	160°
Colours:	Warm White 2,700K
Refresh rate:	< 1,000 Hz
Strobe:	0 - 20 Hz
CRI:	95.8 Ra
TM30:	
Light Output	Light output @ 160° 2m: 670 lux 4m: 230 lux 6m: 118 lux

Electrical

Fixture rated power:	85W
LED engine:	120 x White SMD LED
Input power:	100 - 240V ~ 50/60Hz Auto switching power supply
In/Link:	powerCON TRUE 1 max. link current 10A
Power Factor:	0.97
LVI:	n/a

Environmental

Cooling:	Electronic heat control
IP rating:	IP20
Max. environment temperature:	40°

Accessories

Included	Barndoors (fixed), Filter frame, Soft Frost, Intensifier, powerCON True1
Optional	B SNAP120, B GRID120