

B PAR360Z



SPECSHEET

7 x 60W RGBW LED zoom par



The B PAR360Z redefines the standards for IP-rated zoom pars with its 7x60W RGBW LED engine, capable of producing captivating colors and brilliant illumination. This fixture is distinguished by its rapid zoom capability and high saturation colors, providing dynamic lighting options for events and productions.

With an unmatched power-to-size ratio, the B PAR360Z offers creative freedom in designing lighting setups, ensuring that it can meet the demands of professionals looking for impactful and versatile lighting solutions. Its market-leading output and adaptability make it an essential tool for elevating lighting designs.



Physical

Dimensions (WxHxD):	450 x 297 x 217 mm 17.7 x 11.7 x 8.5 in
Packaging dimensions (WxHxD):	510 x 360 x 265 mm 20.7 x 14.1 x 10.4 in
Net weight:	6.90 kg 15.2 lb
Gross weight:	7.60 kg 16.75 lb
Outer packaging gross weight:	13 kg 28.66 lbs (2 Pcs)
Outer packaging dimensions:	575 x 380 x 540 mm 22.6 x 15 x 21.25 in (2 Pcs)

Mounting options

Hanging:	1 x Omega bracket with 2 x 1/4 turn quick-locks and 1 x M12 hole
Second suspension:	1 x Moulded eye on the housing to pass a safety wire or carabiner
Standing:	Double bracket adjustable opening angle

Control

Menu control:	TFT display with 4 buttons
Control:	DMX512, manual, master/slave
In/Link:	XLR 5-pin
DMX Mode:	5/8/12/17 channels
Dimming:	8-bit
Dimming curve	3 curves (Inv. Square law, Linear, Square law)
Tilt locking system:	One hand tilt locking

Optical

Beam angle:	4.3° - 45°
Colours:	Red, Green, Blue and White
Refresh rate:	600 Hz - 9,600 Hz

Light Output	Light output @ 45° 2m: 4,200 lux 4m: 1157 lux 6m: 562 lux
--------------	---

Electrical

Fixture rated power:	370W
LED engine:	7 x 60W SMD LED RGBW 4 in 1
Input power:	100 - 240V ~ 50/60Hz Auto switching power supply
In/Link:	powerCON TRUE 1 max. link current 10A
Power Factor:	0.94
LVI:	n/a

Environmental

Cooling:	Electronic heat control
IP rating:	IP65
Max. environment temperature:	40°

Accessories

Included	powerCON True1, Omega bracket, Frost filter
Optional	n/a